INSTRUMENT APPROACH CHART - ICAO

LONDON LUTON SRA RTR 2NM RWY 08
(ACFT CAT A,B,C,D)

MSA 25NM NDB(L) LUT (180° 2₀ 2₀ 270° 090° 2₂ 2₁ 360°)	APP	129.550, 128.750	LUTON RADAR	AD ELEVATION **526**
	TWR	132.550, 126.725	LUTON TOWER	THR ELEVATION **515**
		121.750	LUTON GROUND	OBSTACLE ELEVATION **920 AMSL** (405) (ABOVE THR)
	RAD	128.750, 129.550	LUTON/ESSEX RADAR	
	ATIS	120.575	ARRIVAL INFORMATION	BEARINGS ARE MAGNETIC

TRANSITION ALTITUDE **6000**



WARNINGS

Aircraft carrying out the missed approach procedure and unable to achieve **2000** by NDB(L) LUT may, during the climb east of NDB(L) LUT, track outside the confines of controlled airspace whilst between **2000** and **2500**.

Intense gliding activity during daylight hours north of and beneath FAT (see note 3).

RADAR ADVISORY HEIGHTS Gradient 4.9%, 297FT/NM

NM	5.0	4.0	3.0 **(SDF)**	2.0
ALT(HGT)	**2000**(1485)	**1700**(1185)	**1410**(895)	**1110**(595)

Initial and intermediate approach as directed by radar.



MAPT 1NM after RTR

Climb straight ahead to **NDB(L) LUT** to hold at **3000**, or as directed. Aircraft which achieve **2000** by **NDB(L) LUT** continue climb in the hold. Aircraft unable to achieve **2000** by **NDB(L) LUT** inform ATC and continue climb on **NDB(L) LUT** QDR 076° to **2000** then turn right to **NDB(L) LUT** to hold at **3000** or as directed.

Aircraft Category		**A**	**B**	**C**	**D**	**Rate of descent**	**G/S KT**	160	140	120	100	80
OCA (OCH)	**Procedure**	**990**(475)	**990**(475)	**990**(475)	**990**(475)		**FT/MIN**	790	690	590	500	400
VM(C)OCA (OCH AAL)	**Total Area**	**1000**(474)	**1100**(574)	**1300**(774)	**1300**(774)	**RTR to MAPT**	**MIN:SEC**	0:23	0:26	0:30	0:36	0:45

NOTE 1 Aircraft will normally be required to hold not lower than **3000**.
2 Gliding takes place in ceded airspace north of and beneath LOC. Pilots are warned not to descend below the GP/recommeded descent profile. Page AD 2-EGWW 1-14 refers.

CHANGE: COM.

AERO INFO DATE 1 OCT 09