UNITED KINGDOM AIP AD 2-EGPD-5-1 21 Jul 2016



OUTSIDE THE DESIGNATED ATC SURVEILLANCE MINIMUM ALTITUDE AREA

The minimum altitude to be allocated by the approach surveillance controller will be either the Minimum Sector Altitude, or **1000** above any fixed obstacles:
a) within 5NM of the aircraft*, and
b) within the sector 15NM ahead of and within 20° either side of the aircraft's track*.

*When the aircraft is within 15NM of the radar antennae, the 5NM in a) and the 15NM in b) may be reduced to 3NM and 10NM respectively.

LOSS OF COMMUNICATION PROCEDURES

Continue visually or by means of an appropriate approved final approach aid. If not possible proceed at 2500, or last assigned level if higher, to ADN VOR or NDB(L) ATF as appropriate to the procedure being flown†.

Intermediate and Final Approach

Continue visually or by means of an appropriate final approach aid. If not possible follow the Missed Approach Procedure to ADN VOR or NDB(L) ATF as appropriate to the procedure being flown†.
† In all cases where the aircraft returns to the holding facility the procedure to be adopted is the Radio Failure Procedure detailed at ENR 1.1.3.

GENERAL INFORMATION

- Levels shown are based on QNH.

 Only significant obstacles and dominant spot heights are shown.

 The minimum levels shown within the ATC Surveillance Minimum Altitude Area are in conformance with the Standard European Rules of the Air SERA.5015.

 Minimum Sector Altitudes are based on obstacles and spot heights within 25NM of the Aerodrome Reference Point.

 Controlled airspace with a base in excess of 5000 or FL55, as appropriate, is not shown.

 This chart should only be used for the cross-checking of assigned altitudes whilst in receipt of an ATC Surveillance service.

CHANGE (8/16): MAG VAR. OBSTACLES.

AERO INFO DATE 11 MAY 16

CIVIL AVIATION AUTHORITY AMDT 8/2016