

Instrument Approach Procedure Coding Tables

Tiree RNAV(GNSS) RWY 05 - Instrument Approach Procedure via RIMEV

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
RW05R	001	IF	RIMEV	N	-	-	<u>2000</u>	-	562050.57N 0070108.03W	IAF
RW05R	002	TF	PU05I	N	341° (337.1°)	RIGHT	<u>1600</u>	-	562403.65N 0070334.89W	IF / 8.3 NM
RW05R	003	TF	PU05F	N	051° (047.0°)	-	<u>1600</u>	-	562626.39N 0065858.04W	FAF / 4.8 NM
RW05R	004	TF	RW05	Y	051° (047.0°)	-	-	-	562940.97N 0065240.34W	MAPt
RW05R	005	CF	PUM01	N	051° (047.1°)	LEFT	-	-	563203.53N 0064802.51W	-
RW05R	006	TF	PUM02	N	321° (317.1°)	LEFT	-	-	563436.97N 0065220.97W	-
RW05R	007	TF	GIVGI	Y	230° (226.2°)	-	2000	-	562538.99N 0070911.56W	Hold

Tiree RNAV(GNSS) RWY 05 - Instrument Approach Procedure via ATMUM

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
RW05C	001	IF	ATMUM	N	-	-	<u>2000</u>	-	562140.90N 0070811.45W	IAF
RW05C	002	TF	PU05I	N	051° (047.0°)	-	<u>1600</u>	-	562403.65N 0070334.89W	IF / 8.3 NM
RW05C	003	TF	PU05F	N	051° (047.0°)	-	<u>1600</u>	-	562626.39N 0065858.04W	FAF / 4.8 NM
RW05C	004	TF	RW05	Y	051° (047.0°)	-	-	-	562940.97N 0065240.34W	MAPt
RW05C	005	CF	PUM01	N	051° (047.1°)	LEFT	-	-	563203.53N 0064802.51W	-
RW05C	006	TF	PUM02	N	321° (317.1°)	LEFT	-	-	563436.97N 0065220.97W	-
RW05C	007	TF	GIVGI	Y	230° (226.2°)	-	2000	-	562538.99N 0070911.56W	Hold

Tiree RNAV(GNSS) RWY 05 - Instrument Approach Procedure via GIVGI

Designator	Sequence Number	Path Terminator	Waypoint Name	Fly-over	Course/Track °M (°T)	Turn Direction	Level Constraint	Speed Constraint	Co-ordinates	Remarks and Distance to MAPt
RW05L	001	IF	GIVGI	N	-	-	<u>2000</u>	-	562538.99N 0070911.56W	IAF
RW05L	002	TF	PU05I	N	121° (117.0°)	LEFT	<u>1600</u>	-	562403.65N 0070334.89W	IF / 8.3 NM
RW05L	003	TF	PU05F	N	051° (047.0°)	-	<u>1600</u>	-	562626.39N 0065858.04W	FAF / 4.8 NM
RW05L	004	TF	RW05	Y	051° (047.0°)	-	-	-	562940.97N 0065240.34W	MAPt
RW05L	005	CF	PUM01	N	051° (047.1°)	LEFT	-	-	563203.53N 0064802.51W	-
RW05L	006	TF	PUM02	N	321° (317.1°)	LEFT	-	-	563436.97N 0065220.97W	-
RW05L	007	TF	GIVGI	Y	230° (226.2°)	-	2000	-	562538.99N 0070911.56W	Hold

CHANGE (9/16): MAG TRACKS. HOLD LEVEL CONSTRAINT.

AERO INFO DATE 25 MAY 16