

OPERATIONAL MINIMA

CAN THO WEATHER MNM
VVCT

TAKE – OFF MINIMA FOR RWY 06/24

RWY	ACFT CAT	Ceiling (m)	Visibility (m)
06/24	A, B, C, D		600

Note:

1. Take-off alternate aerodromes:
- For international flights: Tan Son Nhat
- For domestic flights : Tan Son Nhat, Rach Gia, Phu Quoc.
2. When the ACFT can not choose any take-off alternate aerodromes as mentioned above, the landing minima as indicated in the below table will be applied to take-off minima.

LANDING MINIMA FOR RWY 06/24

VOR/DME approach procedure for RWY 06	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	135	1 500
	C, D	135	1 700

VOR/DME approach procedure for RWY 24	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	135	1 800
	C, D	135	2 000

VOR/DME/ILS approach procedure for RWY 06	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	60	800
	C	61	800
	D	64	800

Circling RWY 06 and RWY 24	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	200	2 400
	C, D	300	3 000

VOR/DME/ILS approach procedure for RWY 06 In case of GP unserviceable	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B, C, D	135	1 700