

OPERATIONAL MINIMA

NOI BAI WEATHER MNM

VVNB

NDB approach procedure for RWY 11L	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	150	1 600
	C	150	2 000
	D	150	2 800
NDB approach procedure for RWY 29R	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	200	2 000
	C	250	3 600
	D	250	4 000
ILS y, ILS z approach procedures for RWY 11R CAT I	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B, C, D	60	800 (RVR 550)
ILS y, ILS z approach procedures for RWY 11R CAT II	ACFT CAT	Ceiling (m)	RVR (m)
	A, B, C, D	40	400
ILS y, ILS z approach procedures for RWY 11R in case of GP unserviceable	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	140	1 600
	C	140	2 000
	D	140	2 400
ILS x, ILS y approach procedures for RWY 29L	ACFT CAT	Ceiling (m)	Visibility / RVR (m)
	A, B	80	1 100
	C, D	85	1 100
ILS x, ILS y approach procedures for RWY 29L in case of GP unserviceable	ACFT CAT	Ceiling (m)	Visibility (m)
	A, B	140	2 000
	C	140	2 400
	D	140	2 800
Circling RWY 11L/29R and RWY 11R/29L	ACFT CAT	Ceiling (m)	Visibility (m)
	A	200	2 000
	B	400	4 000
	C	500	5 000
	D	600	6 000