

ALTA

ALTA

RNAV(GNSS) - D


TRANSITION ALTITUDE
7000



MISSED APCH:

ON MAPt TURN LEFT* TO INTERCEPT AND CLIMB
ON COURSE 301° TO AT415. TURN RIGHT DCT
OMOMO. ENTER OMOMO HLDG CLIMBING
TO 5000.

*MAX IAS 185 KT DURING FIRST TURN.



NOTE: *WHEN FOLLOWING CIRCLING LGT USE CAT C MNM.

RECOMMENDED RNAV PROCEDURE CODING

ENAT RNAV(GNSS)-D										
Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	MAG VAR	DIST (NM)	Turn Dir	ALT (FT)	Speed (KT)	VPA/TCH
01	IF	AGUGI	-	-	-	-	-	A5000+	K210-	-
02	TF	AT402	-	024(034.4)	-	4.2	-	A4000+	-	-
02	TF	AT401	Y	024(034.8)	-	7.8	-	-	-	-
03	CF	AT415	Y	301(312.0)	-	-	-	-	K230-	-
04	DF	OMOMO	-	-	-	-	R	-	K230-	-
05	HM	OMOMO	-	266(276.7)	-	1 MIN	R	A5000	-	-

Note: Recommended RNAV procedure coding is based on ARINC 424-15 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.