OMNI-DIRECTIONAL DEPARTURE

RØROS RWY 32

RADIO COMMUNICATION

FAILURE:

Squawk A7600. Climb on track 313 $^\circ$ to 7000 FT, then proceed in the most direct manner possible to join the CPL route, climbing to CPL cruising LVL. ACFT under vectoring shall, after set transponder to A7600, proceed the most direct route to join the CPL route, climbing to the CPL cruising LVL.

CLOSE-IN OBSTACLES:

Terrain in immediate proximity to THR RWY 14 requires more than 10.0% climb gradient,

and must be avoided visually or by other means.

VECTORING/ **DIRECT ROUTING:** When being vectored or cleared for DCT routing, the climb gradient(s) stated in Omni-

directional departure "RESTRICTIONS"-table apply.

DESIGNATOR	ROUTE	RESTRICTIONS	CLIMB TO	CONTACT
OMNI 1F (OMNI- DIRECTIONAL ONE FOXTROT DEPARTURE)	Climb on track 313° to MNM 4000 FT. Start turn according to ATC clearance.	MNM climb gradient of 10.0% (608 FT/NM) to 4000 FT. If unable to comply, inform ATC.	7000 FT.	As instructed by RØROS TWR.

02 APR 2015 Avinor