OMNI-DIRECTIONAL DEPARTURE

SVALBARD/Longyear RWY 28

RADIO COMMUNICATION Square

FAILURE:

Squawk A7600. Climb on track 278° to 3000 FT, then proceed in the most direct manner possible to join the CPL route, climbing to CPL cruising LVL. ACFT under vectoring shall, after set transponder to A7600, proceed the most direct route to join the CPL route,

climbing to the CPL cruising LVL

CLOSE-IN OBSTACLES: Vessels crossing the d

Vessels crossing the departure area can require more than 3.3% climb gradient, and must

be avoided visually or by other means.

VECTORING/ DIRECT ROUTING: When being vectored or cleared for DCT routing, the climb gradient(s) stated in Omni-

directional departure "RESTRICTIONS"-table apply.

ATC CLEARANCE: Departing IFR flights shall obtain ATC clearance from LONGYEAR INFORMATION

NOTE: Vessels higher than 51 m AMSL have not been considered to calculate the minimum climb

gradient.

DESIGNATOR	ROUTE	RESTRICTIONS	CLIMB TO	CONTACT
OMNI 1B (OMNI- DIRECTIONAL ONE BRAVO DEPARTURE)	Climb on track 278° to 3000 FT. Start turn according to ATC clearance.	-	5500 FT	As instructed by LONGYEAR INFORMATION

Avinor 03 MAR 2016