


## SVALBARD

**LONGYEAR**

**RNAV(GNSS) Y RWY 10**

**TRANSITION ALTITUDE**  
**5000**



**IF**  
**LOIYO**

**MISSED APCH:**  
AT MAPtURN\* LEFT DIRECT NESAS.  
ENTER NESAS HOLDING CLIMBING TO 5000.



AT MAPtTURN\* LEFT DIRECT NESAS.  
ENTER NESAS HOLDING CLIMBING TO 5000.

- \*CAT A MAX IAS 100 KT
- \*CAT B MAX IAS 130 KT
- \*CAT C MAX IAS 160 KT
- \*CAT D MAX IAS 185 KT

DIST FAF - MAPt: 5.9

**NOTE:** CIRCLING NORTH OF AD ONLY. \* MNM MISSED APCH CLIMB GRADIENT.

**RECOMMENDED RNAV PROCEDURE CODING**

| <b>ENSB RNAV(GNSS) Y RWY 10</b> |                 |                     |          |               |         |           |          |          |            |         |
|---------------------------------|-----------------|---------------------|----------|---------------|---------|-----------|----------|----------|------------|---------|
| Serial Number                   | Path Descriptor | Waypoint Identifier | Fly-over | Course °M(°T) | MAG VAR | DIST (NM) | Turn Dir | ALT (FT) | Speed (KT) | VPA/TCH |
| 010                             | IF              | NESAS               | -        | -             | -       | -         | -        | A4100+   | K230-      | -       |
| 020                             | TF              | LOLVO               | -        | 167 (174.2)   | -       | 5         | -        | A4000+   | K220-      | -       |
| 010                             | IF              | LALAD               | -        | -             | -       | -         | -        | A4200+   | K230-      | -       |
| 020                             | TF              | LOLVO               | -        | 027 (034.0)   | -       | 5         | -        | A4000+   | K220-      | -       |
| 010                             | IF              | OKDIT               | -        |               |         |           |          | A4400+   | -          | -       |
| 020                             | TF              | LOLVO               | -        | 096 (103.8)   |         | 5         |          | A4000+   | K220-      | -       |
| 030                             | TF              | SB601               | -        | 097 (104.2)   | -       | 5         | -        | A3000+   | -          | -       |
| 040                             | TF              | SB602               | Y        | 097 (104.6)   | -       | 5.9       | -        | -        | -          | -       |
| 050                             | DF              | NESAS               | -        | -             | -       | -         | L        | -        | -          | -       |
| 060                             | HM              | NESAS               | -        | 167 (174.2)   | -       | 1 MIN     | R        | A5000    | K230-      | -       |

Note: Recommended RNAV procedure coding is based on ARINC 424-15 and is provided solely to indicate which procedure design protection areas were used in the Instrument Flight Procedure Design process.