OMNI-DIRECTIONAL DEPARTURE

STAVANGER/Sola **RWY 36**

AD 2 ENZV 4 - 13

RADIO COMMUNICATION

FAILURE:

Squawk A7600. Climb on track 359° to 5000 FT, then proceed in the most direct manner possible to join the CPL route, climbing to CPL cruising LVL. ACFT under vectoring shall, after set transponder to A7600, proceed the most direct route to join the CPL route, climbing to the CPL cruising LVL.

CLOSE-IN OBSTACLES:

Rising terrain at 0,6 NM from THR 18 to the right and obstacles close to the THR 18, require more than 3.5 % climb gradient, and must be avoided visually or by other means

VECTORING/ **DIRECT ROUTING:** When being vectored or cleared for DCT routing, the climb gradient(s) stated in Omni-

directional departure "RESTRICTIONS"-table apply.

DESIGNATOR	ROUTE	RESTRICTIONS	CLIMB TO	CONTACT
OMNI 1H (OMNI- DIRECTIONAL ONE HOTEL DEPARTURE) .	Climb on track 359° to 5000 FT. Start turn according to ATC clearance.	MNM climb gradient 5.2% (316 FT/NM) to 2000 FT to stay within controlled airspace. (For OBST reason MNM climb gradient 3.5% to 2000 ft. (213 FT/NM)) If unable to comply, inform ATC.	5000 FT	When instructed by Sola TWR, contact Sola APP 119,6 MHz.

08 DEC 2016 **Avinor**