OMNI-DIRECTIONAL DEPARTURE

STAVANGER/Sola **RWY 18**

RADIO COMMUNICATION

FAILURE:

Squawk A7600. Climb on track 179° to 5000 FT, then proceed in the most direct manner possible to join the CPL route, climbing to CPL cruising LVL. ACFT under vectoring shall, after set transponder to A7600, proceed the most direct route to join the CPL route, climbing to the CPL cruising LVL.

Rising terrain, from RWY 36 to 0.7 NM from RWY 36, require more than 3.3% climb **CLOSE-IN OBSTACLES:**

gradient, and must be avoided visually or by other means

VECTORING/ When being vectored or cleared for DCT routing, the climb gradient(s) stated in Omni-

DIRECT ROUTING: directional departure "RESTRICTIONS"-table apply.

DESIGNATOR	ROUTE	RESTRICTIONS	CLIMB TO	CONTACT
OMNI 1G (OMNI- DIRECTIONAL ONE GOLF DEPARTURE)	Climb on track 179° to 5000 FT. Start turn according to ATC clearance.	MNM climb gradient 6.0% (365 FT/NM) to 2000 FT to stay within controlled airspace and/or due to ATC restriction. (For OBST reason MNM climb gradient 3.3% (201 FT/NM)) If unable to comply, inform ATC.	5000 FT	When instructed by Sola TWR, contact Sola APP 119,6 MHz.

08 DEC 2016 **Avinor**