

KYIV/Boryspil
RNAV_(GNSS, DME/DME) RWY 36L



- BEARINGS AND TRACKS ARE MAGNETIC,
ALTITUDES, HEIGHTS AND ELEVATIONS ARE IN METRES,
DISTANCES ARE IN KILOMETRES

1. CDO are performed during period of low traffic density at ATC discretion.
2. After receiving a "WHEN READY DESCEND TO (LEVEL)" or "DESCEND TO (LEVEL) AT PILOTS DISCRETION" clearance the pilot is free to plan/optimize the vertical profile in order to apply CDO technique up to the FAP.
3. Specified minimum level at waypoint must be adhered unless specifically cancelled by ATC.
4. Maintain MAX IAS 220 kt at a distance of 20 track miles from touchdown.
5. When radar vectors are issued or expected, ATC will provide an estimated track distance from touchdown.
6. For operational regulations refer to UKBB A 2.22 and ENR 1.5.

RNAV ARRIVAL PROCEDURE

RNAV 1 (GNSS, DME/DME) RWY 36L

Name	Path description	Fix identifier (Waypoint name)	Flyover	Course °M (°T)	Turn direction	Altitude	Speed limit
AMKAB 3V AMKAB THREE VICTOR	IF	AMKAB	-	-	-	+ FL220	-
	TF	ASVEN	N	351 (357,9)	-	-	-
	TF	CY	N	349 (355,6)	L	+ 1500	-
	TF	BB656	N	302 (309,4)	L	-	-
	TF	BB654	N	256 (263,2)	L	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
GOTAP 1V GOTAP ONE VICTOR	TF	BB632	N	348 (355,4)	L	900	-
	IF	GOTAP	-	-	-	+ 3050	-
	TF	BB658	N	256 (263,2)	-	+ 1850	-
	TF	BB656	N	256 (263,2)	-	-	-
	TF	BB654	N	256 (263,2)	-	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
KONIP 3V KONIP THREE VICTOR	TF	BB632	N	348 (355,4)	L	900	-
	IF	KONIP	-	-	-	+ 3050	-
	TF	ASVEN	N	346 (353,4)	-	-	-
	TF	CY	N	349 (355,6)	R	+ 1500	-
	TF	BB656	N	302 (309,4)	L	-	-
	TF	BB654	N	256 (263,2)	L	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
KUAL 3V KUAL THREE VICTOR	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-
	IF	KUAL	-	-	-	+ FL120	-
	TF	BBN01	N	159 (166,3)	-	+ FL120	-
	TF	BBE04	N	181 (188,2)	R	+ 2150	-
	TF	INVAD	N	181 (188,2)	-	+ 1500	-
	TF	BB654	N	217 (223,6)	R	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-

Name	Path description	Fix identifier (Waypoint name)	Flyover	Course °M (°T)	Turn direction	Altitude	Speed limit
NANIR 3V NANIR THREE VICTOR	IF	NANIR	-	-	-	+ FL110	-
	TF	BB674	N	144 (150,9)	-	+ 2150	-
	TF	BB672	N	144 (150,9)	-	+ 1850	-
	TF	BB670	N	162 (168,9)	R	+ 1200	407km/h(220kt)
	TF	BB668	N	176 (182,6)	R	+ 900	-
	TF	BB665	N	176 (182,6)	-	+ 900	-
	TF	BB664	N	176 (182,6)	-	+ 900	-
	TF	BB662	N	176 (182,6)	-	+ 900	-
	TF	BB660	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	086 (092,6)	L	+ 900	-
	TF	BB640	N	356 (002,6)	L	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-
NEMIP 3V NEMIP THREE VICTOR	IF	NEMIP	-	-	-	+ FL120	-
	TF	BBN01	N	201 (207,6)	-	+ FL120	-
	TF	BBE04	N	181 (188,2)	L	+ 2150	-
	TF	INVAD	N	181 (188,2)	-	+ 1500	-
	TF	BB654	N	217 (223,6)	R	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-
SLV 1V Soloviivka ONE VICTOR	IF	SLV	-	-	-	+ FL110	-
	TF	BBW01	N	057 (064,4)	-	+ 2750	-
	TF	BB672	N	102 (109,2)	R	+ 1850	-
	TF	BB670	N	162 (168,9)	R	+ 1200	407km/h(220kt)
	TF	BB668	N	176 (182,6)	R	+ 900	-
	TF	BB665	N	176 (182,6)	-	+ 900	-
	TF	BB664	N	176 (182,6)	-	+ 900	-
	TF	BB662	N	176 (182,6)	-	+ 900	-
	TF	BB660	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	086 (092,6)	L	+ 900	-
	TF	BB640	N	356 (002,6)	L	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-
SULUM 3V SULUM THREE VICTOR	IF	SULUM	-	-	-	+ FL170	-
	TF	ASVEN	N	042 (049,3)	-	-	-
	TF	CY	N	349 (355,6)	L	+ 1500	-
	TF	BB656	N	302 (309,4)	L	-	-
	TF	BB654	N	256 (263,2)	L	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-

Name	Path description	Fix identifier (Waypoint name)	Flyover	Course °M (°T)	Turn direction	Altitude	Speed limit
VEBIX 1V VEBIX ONE VICTOR	IF	VEBIX	-	-	-	+ 2450	-
	TF	CY	N	302 (309,4)	-	+ 1500	-
	TF	BB656	N	302 (309,4)	-	-	-
	TF	BB654	N	256 (263,2)	L	+ 1200	407km/h(220kt)
	TF	BB652	N	176 (182,6)	L	+ 900	-
	TF	BB650	N	176 (182,6)	-	+ 900	-
	TF	BB648	N	176 (182,6)	-	+ 900	-
	TF	BB646	N	176 (182,6)	-	+ 900	-
	TF	BB644	N	176 (182,6)	-	+ 900	-
	TF	BB642	N	266 (272,7)	R	+ 900	-
	TF	BB640	N	356 (002,6)	R	+ 900	-
	TF	BB638	N	356 (002,6)	-	+ 900	-
	TF	BB636	N	356 (002,6)	-	+ 900	-
	TF	BB634	N	356 (002,6)	-	+ 900	-
	TF	BB632	N	348 (355,4)	L	900	-

RNAV HOLDINGS

Fix identifier (Waypoint name)	Inbound Track °M (°T)	Turn direction	Minimum Altitude	Time MIN	Distance	Speed limit
BB640	356 (002,6)	R	900	1	-	407km/h(220kt)
BBN01	187 (194,0)	L	1850	1	-	-
CY	302 (309,0)	R	1200	1	-	-
GOTAP	266 (273,0)	L	1850	1	-	-
NANIR	137 (144,0)	L	1200	1	-	-
SLV	058 (065,0)	L	1850	1	-	-
VEBIX	300 (307,0)	L	1850	1	-	-

WAYPOINTS

Waypoint name	Coordinates		Waypoint name	Coordinates	
BB632 (FAF)	501125.0N	0305211.5E	BB670	501159.0N	0304509.0E
BB634	500745.0N	0305239.0E	BB672	501828.0N	0304310.0E
BB636	500345.0N	0305222.0E	BB674	502949.0N	0303318.0E
BB638	495945.0N	0305205.0E	BBE04	503153.0N	0311828.0E
BB640	495545.0N	0305148.0E	BBN01	505041.0N	0312243.0E
BB642	495145.0N	0305131.0E	BBW01	502417.0N	0301718.0E
BB644	495131.0N	0305918.0E	ASVEN	495706.0N	0312422.0E
BB646	495531.0N	0305935.0E	INVAD	502200.0N	0311614.0E
BB648	495931.0N	0305952.0E	CY	500406.0N	0312332.0E
BB650	500331.0N	0310009.0E	SLV	501112.5N	0293412.5E
BB652	500731.0N	0310026.0E	AMKAB	481306.0N	0313020.0E
BB654	501131.0N	0310043.0E	GOTAP	501518.0N	0314912.0E
BB656	501206.0N	0310819.0E	KONIP	494442.0N	0312636.0E
BB658	501358.0N	0313204.0E	KUVAL	514847.0N	0310026.0E
BB660	495159.0N	0304344.0E	NANIR	505000.0N	0301542.0E
BB662	495559.0N	0304401.0E	NEMIP	520413.0N	0322311.0E
BB664	495959.0N	0304418.0E	SULUM	493328.0N	0304133.0E
BB665	500359.0N	0304435.0E	VEBIX	494934.0N	0315109.0E
BB668	500759.0N	0304452.0E			

INTENTIONALLY LEFT BLANK
СТРАНИЦА НАМЕРЕННО ОСТАВЛЕНА НЕЗАПОЛНЕННОЙ